



VP-ASP Shopping Cart

Database Tables

Version 6.08

May 23, 2006

© Rocksalt International Pty Ltd
support@vpasp.com
www.vpasp.com

1 Database

This is a summary of the database fields and tables in shopping600.mdb. Items in Red have been changed in VP-ASP 6.08.

Tables	Description
affiliatelog	Log affiliate entries
affiliates	Affiliate details (requires VP-ASP option package)
billing	Recurring Billing
categories	Holds all the categories of products
coupons	Discount Coupons
content	Used for dynamic site content
configuration	VP-ASP Configuration
currencyvalues	Store different currency types available for the store
customerprices	Customer based pricing table
customers	Each time a customer orders a product(s) a record is stored in the database. Even if the customer cancels the order, the customer information is not deleted
downloads	Used with secure download facility
gifts	Gift Certificates
hackers	Place to store hacker e-mail addresses and IP address
insurancemethods	Used to store different insurance methods for orders
languages	Shop languages
menuitem	The top navigation bar is created based on the data in this table
mycompany	Describes details about the merchant. Used to print merchant details on printed orders
oitems	One row for each item ordered. If multiple products are ordered in a single transaction, there are multiple rows in the database.
orders	The order information is stored here
ordertracking	Tracking messages
pinnumbers	Used with pin number add-on
prodcategories	Lists all categories for a specific product. Used only if the products in multiple categories is used
prodfeatures	Product Features such as color, size or any other attribute
products	The products in the database
projects	Non product services
quantitydiscounts	Quantity discount table
registrant	Gift registry customer details
registryitems	Gift registry items
reviews	Reviews of products by customers and suppliers
savedcarts	Wish list values
searchresults	Search term recording
shipmethods	Different shipping methods and prices
sitesessions	Used for cookieless processing
suppliers	Supplier details
tblaccess	Access rights for users
tbllog	User login to admin system
tbluser	Userids and passwords for admin system
templates	Instead of storing template files on the server, it can be stored here
translatecategories	Descriptions of categories in other languages
translatecontent	Stores page contents in other languages
translateprodfeatures	Stores product feature captions and descriptions in other languages
translateproducts	Stores product details in other languages
ups_config	Configuration details for the in-built UPS facility

1.1 Affiliatelog

Used to record affiliate links to your site.

Afflogid	Unique Id
Affid	Affiliate number
Affdate	Date of line
Afftime	Time of Link
Affdirecturl	Page directed to
Affreferrer	The referring URL
Affcookie	Yes/No if cookie read when order was created
Affother1	Unused

1.2 Affiliates

Affid	Affiliate number
Firstname	
Lastname	
Address	
City	
State	
Postcode	
Country	
Company	
Phone	
Website	
Mobilephone	
Fax	
Email	
Comment	Unused
Logincount	Number of times affiliate linked to site
Logindate	Last link date
Affother1	Unused
Affother2	Unused
Affother3	Unused
Commissionrate	The percentage rate for commission
Orders	Unused
Totalcommission	Unused
Typeofpayment	Hoe affiliate wants to be paid
Bank	Bank name
Bankaccount	
Bankaddress	
Bankother	
Password	Affiliate password
Referralid	On two tier affiliates this is the higher affiliate affid
Mastercommissionrate	On two tier affiliates this is higher affiliate commission rate
Template	

1.3 Billing

This is a control table. It is used to determine how many bills to send out, how often, at what interval.

billamount	How much to bill each interval
billnextbilldate	The date to start the billing
billcustomer	Customer's name
billemail	E-mail address of the customer
billdescription	The description of what the bill is for such as the product or service
billinstallments	A number representing the number of installments. For example 12 will mean that this customer should be billed 12 times.
billinstallmenttype	One of the following words: Day, week, Month, Year For example if Month is in this field, the person will be billed once per month for 12 months.
billinterval	A number such as 1. This is the interval between bills in the same units as above.
billcreationdate	Date you are creating this billing record
billenddate	Optional. The last date for which a bill should be sent out. If not supplied VP-ASP stops sending bills when the installments are completed.
billorderid	It is the original order that caused this billing record to be created
billlastmaildate	The date the last bill was sent out
billsentcount	The number of e-mail bills that have been sent to the customer
billcanceled	If True, then the merchant has decided to stop sending bills to the customer
billcompleted	If true, it means that this billing record is no longer used since all installment e-mails have been sent. It is normally set by VP-ASP automatically after the last installment is sent
billcreationdate	The date this billing record itself was created.
billorderitemid	The record number in the oitems table for the original order that created the billing record
billenddate	Used to stop billing at a certain date regardless of whether the number of installments has been reached. Normally this field would not be used
billtemplate	Optional. Used to specific a unique mailing template for bills generated from this billing record
billother1	Unused
billother2	Unused

1.4 Categories

The products database must have at least one category. These are displayed by shopdisplaycategories.asp.

Categoryid	unique id
Catdescription	Description
catextra	If filled in, it is the name of a file to be used to display when products for this category are displayed
Hassubcategory	If not null, then subcategories will be displayed for this category
Catimage	Image to display for this category
Highercategoryid	0 if highest category. Otherwise the categoryid of the higher category
Cathide	Any value means hide this category
Catmemo	Text to display when category is displayed
Productmatch	Used to display products depending on site
Customermatch	Used to display products based on customer login
Catlanguage	Language to be displayed
Catproducttemplate	Template for product displays
Impressions	The number of times this category was viewed

1.5 Configuration

id	unique id
Fieldname	Shop Configuration name
Fieldvalue	Value
Fieldgroup	Grouping for menu displays
Fieldyesno	Yes or No value field
Message	Used to display help message for configuration
showfield	Where to show or hide the configuration field
fieldgroup2	Redefine field group in new configuration mode

1.6 Content

Conentid	unique id
Messagestype	Used to distinguish different types f content
Message	Description
Message2	Additional description. Optional
Image	Image
Hide	Hide this content message
Template	Template to be used. Optional
language	Language of this template
Other1	Unused
Other2	Unused
Other3	Unused
loggedin	Show content only to logged in users
impressions	Number of times the content page was accessed
cdateadded	When the content was added
cdateupdated	When the content was updated

1.7 Currencyvalues

id	unique id
cid	Text id of the currency unit
Fullunitname	Full description of currency unit
Conversionvalue	Conversion rate relative to the base currency
Theimage	Image to represent the currency unit
Hide	Hides the currency type in the shop

1.8 Customerprices

id	unique id
Customerid	Customerid matches contacted in customer record
Categoryid	Category of product to be discount
Catalogid	Catalogid if product to be discounted
Discountpercent	A number like .10 which is the percent discount
Discountamount	A number like 20 which is the amount of the discount

1.9 Coupons

Coupons can be used to give a discount for all or selected products. Coupons work only with the VP-ASP Option Package

couponid	Unique id
couponname	
couponpercent	The percent discount. For example .10 for 10%
couponamount	Actual amount in dollars
couponexpires	Date of expiration
couponlimit	Number of times coupon can be used
couponcomment	Unused
couponother	Unused
couponcategories	Optional. List of category numbers to which coupon applies 1,7,3
couponproducts	Optional. List of product catalogids to which discount applies 23,77,66
couponusedcount	Updated by VP-ASP each time a coupon is used
Couponuseddate	Last date coupon was used
Couponcustomers	List of customerids for which coupon is valid 88,55,3
Couponminimum	The minimum amount to be purchased before coupon can be used
couponaffid	Associate a coupon with an affiliate

1.10 Customers

Most of the fields in this table are self explanatory.

contactid	Unique Id
firstname	
lastname	
Address	
City	
State	
postcode	
country	
company	
phone	
workphone	Unused
mobilephone	Unused
Fax	Unused
Email	Required
Contactypeid	Used for customer based pricing. A number that represents the customer type
Comments	Unused
Contactreason	Filled in when customer registered via mailing list
Logincount	Updated each time the user uses the shoplogin script.
lastlogindate	Last date user logged in to buy something
Website	Customer web site
Password	Password for the user
Discount	The discount to be applied to customer. If less than 0 it is a percent, if > 0 it is a dollar amount.
custoother1	Unused
Accountno	Unused
Cardno	Unused
Cardexpires	Unused
Cardname	Unused
Cardaddress	Unused
Cardcvn	Unused
Maillist	TRUE/False whether customer wants to be on mailing list
Productgroup	Used to match customers to specific products
cookiequestion	Yes/No. Does customer want info saved as a cookie
pointstotal	Total points accumulated
pointsremaining	Number of points remaining
Vatnumber	VAT number
Userid	Customer userid
Hearaboutus	Text. How customer heard about your company
Address2	Second address field
Taxexempt	Specify if the customer is exempt from tax

1.11 Downloads

Id	unique id
Ordered	Order number for this download
Catalogid	Product catalogid
Customerid	Customerid
Filename	Filename to be downloaded
Downloadcount	Number of times product has been downloaded
Downloadmaxcount	Maximum download limit
Downloaddatelimit	Last date download is allowed
Downloadcreatedate	Date this record was created
Downloadother	Unused
Downloadother1	Unused
Authorized	Not null means this download is authorized
Lastdownloaddate	Last date file was downloaded

1.12 Gifts

Gifted	unique id
Giftnumber	Generated gift number
Giftissuedate	Date gift record created
Giftauthorized	If it is not empty, then gift certificate can be used
Giftamount	Initial amount
Giftamountremaining	Amount remaining
Giftorderid	Order number that created gift record
Gifttoname	Name of recipient
Giftfromname	Sender
Gifttoemail	Email of receiver
Giftmessage	
Giftfromemail	Email of sender
Giftuseddate	Last time gift was used
Giftusedcustomerid	Customer record of user
Giftusedlastamount	Last amount used
Giftusedorderid	Last used ordered
Giftother	Unused
Giftexpirydate	Last date gift can be used
Giftusedcount	Number of times gift was used
Giftusedtrace	Trace record of order and amounts

1.13 Hackers

Hackerid	Unique Id
Ipaddress	In the form 55.23.94.99
Emailaddress	Email address or partial e-mail address
Comment	Unused
Other	unused

1.14 Insurancemethods

insurancemethodid	Unique Id
Insurancemethod	Text description of insurance method
Insuranceprice	Price of insurance
Insurancebasecost	
Insuranceextracost	
Insuranceother1	
Insuranceother2	
Insurancecost1	
Insurancecost2	
Insuranceroutine	
insurancecountry	

1.15 Languages

id	Unique Id
Lang	Language name such as English
Keyword	Used internally such as Langcommoncontinue Do not change these names
Caption	Actual text of the phrase

1.16 Menuitem

id	Unique Id
Name	Display name of the menu item
Seq	Determines what order this menu item will appear in the menu
Pmenuitemid	If the menu item is to be in a dropdown sub-menus, you need to specify which top level item it should appear below.
Url	Url to the page you want to link to
Contentid	Unique id of content to link to
Openin	Open page in same or new window

1.17 Mycompany

setupid	Unique Id
Companyname	
Address	
City	
State	
Postalcode	
Country	
Phonenumber	
Faxnumber	
Myemail	
Other1	Unused by VP-ASP
Other2	Unused by VP-ASP
Other3	Unused by VP-ASP
Other4	Unused by VP-ASP

1.18 Orders

Most of the fields are self explanatory. Many are taken directly from the customer table and repeated here.

Ordered	Unique Id
Ocustomerid	Index back to Customer record
odate	Order Date
Orderamount	Total Price
Ofirstname	
Olastname	
Oemail	
Oaddress	
Ocity	
Opostcode	
Ostate	
Ocountry	
Ophone	
Ofax	
Ocompany	
ocardtype	Credit Card type
ocardno	Card Number
ocardname	Name on Credit Card
ocardexpires	Expiry date in form mm/yy
ocardaddress	Credit Card Address
oprocessed yes/no	0 = unprocessed, 1=processed
ocomment	User order special instructions
otax	Tax
opromisedshipdate date	Unused
oshippeddate date	Unused
oshipmethod	Unused
oshipcost	Shipping cost
oshipname	Shop to name
oshipcompany	
oshipemail	
oshipmethodtype	Shipping method in words
oshipaddress	
oshiptown	
oshipzip	
oshipstate	
oshipcountry	
opaymethod	Unused
other1	Unused
other2	Unused
otime	Time of order
oauthorization	Authorization code for credit card banking systems
oerrors	Any table add errors are placed here. New 2.40
odiscount	The actual discount amount given to the customer
ostatus	Status of the order. This needs to be manually completed by the merchant.
oaffid	The unique affiliate number associated with this order
odualtotal	Dual Price total
odualtaxes	Dual Price taxes
odualshipping	Dual price shipping cost
odualdiscount	Dual price discount
ohandling	Handling Price
odualhandling	Dual Handling Price
coupon	Text name of coupon used for purchase
coupondiscount	Amount of discount

coupondiscountdual	Dual Discount Coupon amount
giftcertificate	Gift Certificate used
giftamountused	Amount of Gift certificate
giftamountuseddual	Dual currency amount used
canceled	Set to True if order was canceled.
opaddress	IP address of site from which the order was made
Hackeryesno	Yes/No whether this person is a hacker. Not set automatically and is unused by Vp-ASP
customercancel	Unused.
Points	Points for this order
Vatnumber	VAT number used
Commission	Affiliate commission
Opening	Order pending status
Shipmessage	Special shipping message
Oaddress2	Second customer address
Oshipaddress2	Second shipping address
Deliverydate	Delivery date
Deliverytime	Delivery time
Producttotal	Product only total
Oinsurancemethodtype	Text description of insurance type
Oinsurancecost	Cost of insurance
Oinsurancemethod	Unique ID of insurance method
Odualinsurance	Cost of insurance when dual pricing is on
Upstrackno	Tracking number issued by UPS

1.19 Oitems

Each order consists of one or more products.

orderid	Unique id
orderid	The index representing the specific order=OrderId
catalogid	The index representing the specific product catalogid
numitems	Quantity
itemname	The Product Name. The name may include product options.
unitprice	The Unit Price.
dualprice	The dual price for this item
supplierid	Number of supplier in suppliers table
Address	Delivery address. Fields are delimited by semicolons
Pinnumber	Used with pin number add-on

1.20 Ordertracking

trackid	Unique id
orderid	Order number
trackcomment	Comment/message
trackdate	date
tracktime	time
trackname	Person making comment
trackview	Allow customer to view yes/no
trackother	Unused
trackemail	E-mail of person making comment

1.21 Pinnumbers

serialid	Auto number generated
catalogid	The associated product catalogid for this record
pinnumber	The pin number to be used
ordered	Automatically filled in when the pin number is used
pinproductmatch	If the catalogid field is not used to match the product record. This is the field name to be used in the match. It is assumed to be a text field. For example ccode
pinother1	Unused

1.22 ProdFeatures

Products may or may not have features such as color or size. These are defined in this table.

Id	Unique Id
featurenum	Feature Group Number
featurecaption	Feature Group caption that is displayed above drop down list
featurename	The feature name displayed in drop down list
featureprice	Feature price or null or 0
featureother	Unused expansion field
featuretype	If empty default to dropdown Values can be: dropdown radio checkbox usertext selectlist userprice quantity
featuremulti	leave empty unless multiple different values can be selected. Then set Yes in this field.
featurerequired	True/False whether feature is required
featureother1	Unused
Featureimage	Image for feature
Featureweight	Weight of feature
Featurepercent	Percent of product price to be added
Featuredefault	Whether feature is a default value

1.23 Prodcategories

Used only if products are allowed to be in multiple categories. It relates the products to the categories they are in.

Id	Unique id
intcategoryid	Category number
intcatalogid	product catalog id

1.24 Projects

Pid	Unique id
Pdate	Date entered
description	Short description of service
customer	Customer name
customeremail	Customer e-mail
price	Price to be charged
dualprice	Dual price if used
paid	Set to Yes if paid if using automatic project updating
datepaid	Set to order date if using automatic project updating
processed	determines if automatically displayed on projects report
orderid	order number associated with payment. Updated with order number if using automatic project updating
canceled	Unused
comments	Unused
other1	Unused
other2	Unused
other3	Unused
Billid	Recurring billing identifier
Billdescription	Used for recurring billing

1.25 Products

Holds the individual products.

catalogid	unique id
Ccode	Product Code
Cname	Product Name - required
cdescription	Description- required
Cprice	Price - required
features	An array of numbers such as 1,2,3 meaning features with featurenum 1,2 etc
cimageurl	Image for the product. Will be displayed in shopdisplayproducts
cdateavailable	Date available - unused
Cstock	Stock level
ccategory	Category Number - required. Determines which category a product is in
category	Category Name – no longer used
Mfg	Manufacturer – unused
cdescurl	URL of extended description page. VP-ASP generates hyperlink to this page automatically Only used in shopdisplayproducts
weight	Weight
buttonimage	The name of a gif or jpg file that replaces the standard order button in shopdisplayproducts. mypic.gif
subcategoryid	The number representing the subcategory to which this product belongs
retailprice	Displays under Price in italics
specialoffer	A text field that is bolded under descriptions and products are sorted so special offers appear at the top of the products listing
allowusertext	A caption is entered in this field. This allows the buyer to enter up to 255 characters of information when ordering the product. Obsolete. This is now controlled by ProdFeatures FeatureType. Obsolete and replaced by Usertext feature.
pothor1	Unused
pothor2	Unused
pothor3	Unused
pothor4	Unused
pothor5	Unused
userid	The user who entered the product
keywords	A list of keywords used in searching in the form abc, def
template	If VP-ASP generates the extended description page, this HTML template to be used. If not specified the default template in shop\$config is used
extendedimage	If VP-ASP generates the extended description this is larger image of the product that is displayed instead of the thumbnail
extendeddesc	If VP-ASP generates the extended description page this is the long description of the product. It can have imbedded HTML controls
selectlist	Used to generate a unique selection dropdown list. In the form: big,small,x-large
level3	Unused
level4	Unused
level5	Unused

supplierid	Number of the supplier in the suppliers table
crossselling	A list of catalogids to be displayed when this product is displayed. The format is a list. 27,55,990
hide	If set to TRUE, product is not displayed
productmatch	Used to match products with different VP-ASP directories
customermatch	Used to match customers with products they can "see"
orderattachment	File name with complete drive address to be added to customer confirmation e-mail
orderdownload	File name or URL of file to be generated at completion of the order
points	Number of points for this product
pointstobuy	Unused. For future points redeeming
price2	Unused
price3	Unused
Billprice	Recurring billing amount
Billinstallments	Number of installments
Billinstallmenttype	Day, Week, Month, Year
Billinterval	Interval between installments
Maximumquantity	Maximum number that can be ordered
Frontpage	Determines—if product is displayed on home page
Inventoryproducts	List of catalogids to be used for inventory control
Taxfree	Product is tax free
Freeshipping	Product has free shipping
Highercatalogid	The unique ID of the product this product belongs to
Spdisplaytype	Display type of sub products
Hassubproduct	If the product has sub products
Impressions	Number of times the product was viewed
Cdateadded	When the product was added
Cdateupdated	When the product was updated
Templatelisting	Individual template file for product

1.26 Quantitydiscounts

Id	Unique ID
Categoryid	Discount to apply to products in this category
Catalogid	Discount should apply to this specific product
Minquantity	The minimum quantity before the discount should apply
Quantity1	The upper level of the quantity
Discount1	The amount of discount
Quantity2	The next quantity range
Discount2	The amount of discount for second range
Quantity3	
Discount3	
Quantity4	
Discount4	
Quantity5	
Discount5	
Other	Unused by VP-ASP
Groupfordiscount	Group name to apply a discount across a range of products.

1.27 Registrant

Stores the details of gift registries created. Gift registry work only with the VP-ASP Option Package. Most fields are self explanatory; fields proceeding with “co” are details of the co-registrant, and “send” are for shipping.

Registrantid	Unique ID
Firstname	
Lastname	
Address	
City	
State	
Postcode	
Country	
Company	
Phone	
Workphone	
Mobilephone	
Fax	
Email	
Comments	
Logincount	Number of times the customer has logged into your store
Lastlogindate	This is the last date that the customer logged into your store
Regpassword	Registrant's password for logging in and editing the gift registry
Publicpassword	Public password for logging in and browsing/purchasing items from the registry
Eventdate	Date of when the event will take place
Eventtype	Type of event, e.g. Anniversary, wedding
Eventdateend	
Cofirstname	
Colastname	
Coaddress	
Cocity	
Costate	
Copostcode	
Cocountry	
Cophone	
Coemail	
Sendfirstname	
Sendaddress	
Sendcity	
Sendstate	
Sendpostcode	
Sendcountry	
Sendphone	
Sendemail	
Regdate	Date when the registry was created
Regtime	Time when the registry was created
Thankyounote	Text to display to customers who purchased for this registry
Shippingtype	Shipping type chosen for shipment of the registry items to the registrant
Regorderid	Order ID of the registry
Publicallowed	Whether the general public can access this registry without a password from the registrant
Regother1	Unused by VP-ASP

Regother2	Unused by VP-ASP
Processed	Whether the registry has been completed and shipped to the registrant

1.28 Registryitems

Regitemid	Unique ID
Registrantid	Unique ID of registrant
Orderid	Order ID this registry is associated with
Regcatalogid	The catalog ID of this product
Numitems	Number of this product added to the registry
Itemname	Name of item
Unitprice	Unit price of product
Dualprice	The dual price for this product
Supplierid	ID of the supplier that this product is sourced from
Address	Unused by VP-ASP
Numberpurchased	Number of this item that have been purchased from the registry
Purchaseorderid	Order IDs of the orders that have purchased this item for this registry

1.29 Reviews

ID	Unique ID
Catalogid	ID of product review
Authorized	A flag to determine whether the review has been authorized for display on your site
Reviewdate	Date when the review was submitted
Reviewtime	Time when the review was submitted
Rating	Rating of product
Title	Title of review
Comment	Review of product
Location	Location of reviewer
Name	Name of reviewer
Email	Email of reviewer
Other1	Unused by VP-ASP
Other2	Unused by VP-ASP

1.30 Savedcarts

Id	Unique ID
Cartname	The customer name for this cart
Customerid	The customer number that created the cart
Cartcookies	Actual value of the stored cart
Savedate	Date cart created
Savetime	Time cart was created
Other12	Unused
Catalogid	Catalogid for single product wish list

1.31 Searchresults

Id	Unique ID
Rdate	The date the search was completed
Rtime	The time the search was completed
Categories	Categories that the customer chose to search
Subcategories	Subcategories that the customer chose to search
Words	Words the customer entered to search on
Lastname	Customer's last name (if they were logged in)
Customerid	Customer's customer ID (if they were logged in)
Ippaddress	Customer's IP address
Rother1	Unused by VP-ASP
Rother2	Unused by VP-ASP

1.32 Shipmethods

Depending on the shipping method, the fields will contain information required to calculate the shipping cost of an order.

Shipmethodid	Unique ID
Shipmethod	Name of shipping method
Smprice	Price of shipping method
Shipbasecost	Base cost and are added regardless
Shipextracost	Extra cost applied to shipping based: Quantity/quantity range: multiplied by items Weight: multiplied by the weight you specify on the product and quantity Weight range: multiply by remaining weight
Shipother1	Contains the lower range of quantity or weight range
Shipother2	Contains the higher range of quantity or weight range
Shipcost1	Contains the minimum price in price range
Shipcost2	Contains the maximum price in price range
Shiproutine	File to calculate shipping cost
Shipcountry	Country this shipping method applies to

1.33 Sitesessions

Used for cookieless processing to hold session values

Sessionid	Unique ID
Sessiondate	Date credited
Sessiontime	Time created
Sessionkey	Unique session id
Sessionvalue	Session values
Sessionnow	System time in now format used in cleanup

1.34 Suppliers

supplierid	Unique id
name	Supplier name
supplieruserid	userid
firstname	
lastname	
address	
city	
state	
postcode	
country	
company	
phone	
workphone	
mobilephone	
Fax	
Email	
comments	
logincount	
lastlogindate	
website	
supplierpassword	Password
accountno	Unused by VP-ASP
template	Template for mailing
commissionrate	Commission rate
other1	Unused by VP-ASP

1.35 tblAccess

The Administrative userids have access to various menus. These are described here.

Fldauto	Unique id
Fldname	The name displayed on the menu
Fldurl	The actual URL of htm or asp file to execute
Fldcomment	Displayed by shopadmin.asp on right hand side of menu. New 2.40

1.36 tblUser

fldauto	Unique Id
fldusername	Userid
fldpassword	Password
fldaccess	A list of numbers 1,2,3 relating to tblAccess fldAuto.
flddatabase	Unused
tablesallowed	A string of table names that the user is allowed to view and edit. Customers,Orders,tblUser
admintype	Two types are supported. SUPER and Restricted
uploadirectory	Unused
adminother1	Unused

1.37 tblLog

Each time an administrator does a login into the shopping administration, it is logged here.

fldauto	Unique id
fldusername	Userid
fldtime	Time of login
flddate	Date of Login
fldinout	Values are In for Login
fldipaddress	IP address of administrator login

1.38 Templates

Id	Unique id
Templatename	Name of template
Template	Template code

1.39 Translatecategories

Translateid	Unique id
Lang	Language that this translation belongs to
categoryid	Category ID for the category that this translation is linked to
catdescription	Translated name for this category

1.40 Translatecontent

Translateid	Unique id
Lang	Language that this translation belongs to
content	Content ID for the content that this translation is linked to
Message	Translated text for the message field of the content
Message2	Translated text for the message2 field of the content

1.41 Translateprodfeatures

Translateid	Unique id
Lang	Language that this translation belongs to
id	Feature ID for the feature that this translation should be linked to
Featurecaption	Translated text for the caption field of the feature
featurename	Translated text for the name field of the feature

1.42 Translateproducts

Translateid	Unique id
Lang	Language that this translation belongs to
Catalogid	Catalogid ID for the product that this translation should be linked to
Cdescription	Translated text for the description field of the product
Cname	Translated text for the name field of the product
extendeddesc	Translated text for the more field of the product

1.43 Ups_config

Configurations for the in-built UPS shipping method, most of them are filled during installation.

Upsid	Unique id
Xzeroweighterror	Produce an error when a product with zero weight is selected
Xautoseparateweight	Seperate packages for shipping when weight is above this vvalue
Xautoseparatepackages	Seperate packages for shipping if weight is above the value in the Auto-seperate weight field
Xsuppliershipfield	
Xusesupplierzip	Calculate shipping costs relevant to your suppliers location
Xindividualpackages	Allow certain products to be shipping individually
Ups_weightunits	Unit of weight
Ups_residentialind	PO Boxes will not be accepted
Ups_unitofmeasurement	Unit of measurement
Packagingtype	Packaging type
Pickuptype	Pickup type
Xmerchantcountry	
Xmerchantstate	
Xmerchantcity	
Xmerchantpostcode	
Accesslicencenum	
Username	
Password	
Developerkey	
Gatewaylocation_license	
Gatewaylocation_register	
Xml	XML version to use
Xcheckindividualproductfield	Field in product to use to check for individual packaging
Xcheckindividualproduct	
Xdimensionfield	Field to store dimension in product
Ups_dimensions	
Gatewaylocation_paymenttest	Payment gateway location for testing
Gatewaylocation_payment	Payment gateway location for production
Testmode	Set to testmode
Xupsacctno	UPS account number
Dimensions	
Xtrace	For debugging code
Xtracexml	For debugging XML request and response
Gatewaylocation_trackingtest	Tracking gateway location for testing
Gatewaylocation_tracking	Tracking gateway location for production